

Review of: "Since the structure of carbon nanotubes has different values for the production and reproduction of nanotransistors at different temperatures, it is shown as a function of temperature in the form of $T(\lambda)$ "

Lee Ping¹

¹ Beijing City University

Potential competing interests: No potential competing interests to declare.

In describing nanostructures, it is necessary to distinguish between the number of dimensions in the volume of an object that is on the nanoscale. The surfaces of nanostructures have a nano-scale dimension. Spherical nanoparticles in the nanoscale have three dimensions, that is, the magnifier of each of the spatial dimensions is between 0.1 and 100 nanometers. The terms self-assembly in nanostructures are often used synonymously, although this function can also reach the micrometer range.

Since the structure of carbon nanotubes has different values for the production and reproduction of nanotransistors at different temperatures, it is shown as a function of temperature in the form of $T(\lambda)$. Starting from low temperatures and gradually increasing the temperature it can be seen that the value of $T(\lambda)$ reaches a maximum value of 111.3 mK/W near the temperature of 011 K (this maximum can be seen as a peak in the graph) and then decreases with increasing temperature. The maximum value $(T) \lambda$, which has been observed so far in the investigations, is related to a special nano heat pipe sample that was measured at a temperature of 010 K. This value is equal to 00111 mk/W. Therefore, the value of $(T) \lambda$ nano The carbon tube at its maximum is comparable to the highest value $(T) \lambda$ that has been measured so far. According to the presented diagram, even at room temperature, the thermal conductivity of the carbon nanotube is very high and equal to 0011 mK/W is, in the methods of reproduction of nanotransistors and nanotubes with the synthesis of carbon nanotubes based on catalytic chemical vapor deposition (CCVD), it includes the decomposition of a carbon source on small metal particles or clusters as a catalyst. This method of reproduction of nanotransistors includes a heterogeneous process and it is homogeneous. The metals used for these reactions are transition metals, such as iron, cobalt, and nickel. Compared to electric arc discharge and laser ablation, carbon nanotubes are generally formed at a lower temperature of about 011 to 0111 degrees. Generally, the selectivity of this method is higher for the production of multi-walled carbon nanotubes. Both homogeneous and heterogeneous processes are very sensitive to the nature and structure of the catalyst used in addition to the operating conditions. Compared to the electric arc method, the carbon nanotubes produced by this method have more length (several tens to hundreds of micrometers) and defects. The major drawback of nanotubes is due to the use of lower temperatures

compared to the electric arc method, which does not allow any structural rearrangement.

Conclusion :

Since the structure of carbon nanotubes has different values for the production and reproduction of nanotransistors at different temperatures, it is shown as a function of temperature in the form of $T(\lambda)$.

Starting from low temperatures and gradually increasing the temperature It can be seen that the value of $T(\lambda)$ reaches a maximum value of 111.3 mK/W near the temperature of 011 K (this maximum can be seen as a peak in the graph) and then decreases with increasing temperature .

[1][2][3][4][5][6][7][8][9][10][11][12][13][14][15][16][17][18][19][20][21][22][23][24][25][26][27][28][29][30][31][32][33][34][35][36][37][38][39][40][41][42]

References

- [^] Daniel Milovich. (2023). Review of: "Two-dimensional field effect nanotransistors (ballistic) having a threshold frequency and also greater mobility". Qeios. doi:10.32388/s3tzqq.
- [^] Martin Harisson. (2023). Review of: "(Field effect nano transistors) quantity and ionization potential". Qeios. doi:10.32388/quy19a.
- [^] Linda Brouce. (2023). Review of: "(Field effect nano transistors) Nano transistor electronic quantity". Qeios. doi:10.32388/12sgvj.
- [^] Afshin Rashid. (2023). Review of: "High speed (doping) nMOS graphene transistor in p- and n-doping electronic circuits (positive and negative)". Qeios. doi:10.32388/jreu5m.
- [^] Criystian Orlando. (2023). Review of: "graphene transistor in p- and n-doping electronic circuits". Qeios. doi:10.32388/wsobnd.
- [^] Afshin Rashid. (2023). Review of: "(Field effect nano transistors) Nano transistor electronic quantity and ionization potential)". Qeios. doi:10.32388/464lg7.
- [^] Afshin Rashid. (2023). Review of: "Nano wire immersion method (structure and function)". Qeios. doi:10.32388/0od0gl.
- [^] Anita Gupta. (2023). Review of: "Amplification of Nano Wires Nano Wire by Electron Nano Lithography". Qeios. doi:10.32388/l3md1n.
- [^] Afshin Rashid. (2024). Electrical Nano Biosensors and Measurement of Biological Responses. doi:10.22541/au.172295942.21051561/v1.
- [^] Afshin Rashid. (2024). Changing some properties such as conductivity in electromagnetic properties in nanowires. doi:10.22541/au.172288374.46450261/v1.
- [^] Afshin Rashid. (2024). NEMS and nanotechnologies with high aspect ratio (LIGA-like and LIGA) or (high-aspect ratio). doi:10.22541/au.172288387.75232996/v1.
- [^] Afshin Rashid. (2024). Nano-Biosensors and Nano-Biochips in Moving Nano-Particle Molecules Through Dielectric

- Enhancement Through Vertical Nano-gap Architectures*. doi:10.22541/au.172295948.88883264/v1.
13. ^ Afshin Rashid. (2024). *Biological (Nano-Electro Sensors) and Lab on a Chip Micro-Elements of Diagnostic Laboratories*. doi:10.22541/au.172296107.70762266/v1.
 14. ^ Afshin Rashid. (2024). *Genome Nano Biochip , a Bioelectronic and Microarray Device*. doi:10.22541/au.172296169.96227926/v1.
 15. ^ Afshin Rashid. (2024). *Cadmium Selenide (CdSe) NanoBio Sensors for Detection of Cancer Tumors Using Fluorescence Characteristics*. doi:10.22541/au.172296281.16229663/v1.
 16. ^ Afshin Rashid. (2024). *MEMS Bio Has a Wide Range of Applications in Environmental and Drug Screening and DNA Fragmentation* . doi:10.22541/au.172296308.82234621/v1.
 17. ^ Afshin Rashid. (2024). *Electric Nano Biochips (Nano Biochip) in identification and Decoding (RNA _ DNA)*. doi:10.22541/au.172305736.62150500/v1.
 18. ^ Afshin Rashid. (2024). *Wafer Reproduction of Nanowires Silicone Wafer and Mounting or Growth of Nanowire Particles*. doi:10.22541/au.172305750.07463131/v1.
 19. ^ Afshin Rashid. (2024). *Fabrication of Arrays of Vertically Aligned Cobalt Nanowires on Flat Surfaces as Well as Field Emission (FE)* . doi:10.22541/au.172305753.36343628/v1.
 20. ^ Afshin Rashid. (2024). *Placement of Rectenna Suitable in The Feed Slot Location Electric Nano Antenna Rectenna*. doi:10.22541/au.172315005.57300112/v1.
 21. ^ Afshin Rashid. (2024). *(Nano Telecommunication) The Microstrip Antenna is Designed to Operate at 100 MHz, But Has a Resonance of About 96 MHz*. doi:10.22541/au.172315009.91963570/v1.
 22. ^ Afshin Rashid. (2024). *Performance improvement in Nano dipole L/d in Nano Electric Antennas < a i=4> (Rectenna)*. doi:10.22541/au.172315013.32160951/v1.
 23. ^ Afshin Rashid. (2024). *Communication Between The Feeding System And The Physical Communication Platform Between Different Parts of a Nano System and Nano Antennas (Rectenna)*. doi:10.22541/au.172315025.59177735/v1.
 24. ^ Afshin Rashid. (2024). *FinFET Nanotransistor Downscaling Causes More Short Channel Effects, Less Gate Control, Exponential increase in Leakage Currents, Drastic Process Changes and Unmanageable Power Densities* . doi:10.22541/au.172322868.80518858/v1.
 25. ^ Afshin Rashid. (2024). *nMOS Transistors (Correct Pronunciation: en _ mos) Amplify The Current Depending On The Direction of The Electric Field* . doi:10.22541/au.172322868.86077475/v1.
 26. ^ Afshin Rashid. (2024). *The Switching Efficiency (nMOS transistor) Can Block a Voltage Of Several Hundreds Of Volts With a Few Milliamps* . doi:10.22541/au.172322869.97919381/v1.
 27. ^ Afshin Rashid. (2024). *Theory, modeling and simulation as a predictive design tool widely in the reproduction and fabrication of dynamic molecules of " SWCNT nanotubes and SWCNTs " to produce electric current*. doi:10.22541/au.172348884.40644382/v1.
 28. ^ Afshin Rashid. (2024). *(Nanoelectronics - Plasmonics) Model Experiments With, for Example, Microwaves and Larger Metallic Structures*. doi:10.22541/au.172348884.43902040/v1.
 29. ^ Afshin Rashid. (2024). *Buckminster Fullerene Explanation From The Point Of View Of Nanoscience And Nanoelectronics*. doi:10.22541/au.172357671.12341134/v1.

30. ^ Afshin Rashid. (2024). *(Nanoelectronics - Plasmonic) and The Approach of Nanoplasmonic Technology Towards The Assembly Of Optical Nanoelectronics Circuits.* doi:10.22541/au.172357680.00719708/v1.
31. ^ Afshin Rashid. (2024). *The Growth Mechanism Of CCVD Nanotubes in Production (Nanotransistor - Nanochips).* doi:10.22541/au.172417362.28358373/v1.
32. ^ Afshin Rashid. (2024). *Nano Lithography of Stencil Mask (Resolution up To 20 nm) in The Manufacture of Wafer Nanowires.* doi:10.22541/au.172417363.34910342/v1.
33. ^ Afshin Rashid. (2024). *(Nano Telecommunication) Use of Audio Signals to identify Attractive Molecular Activity ((interaction) Or (Active Orbit))* . doi:10.22541/au.172417541.16082054/v1.
34. ^ Afshin Rashid. (2024). *Strings And Micro-Cylinders of Structured Nanowires (Silicon/Germanium) For Possible Applications in Electronic Energy* . doi:10.22541/au.172417542.21554860/v1.
35. ^ Afshin Rashid. (2024). *Nano Supercapacitor Called (Electrostatic) -- The Total Thickness of Each Electrostatic Nanocapacitor is Only 25 nm.* doi:10.22541/au.172357749.98746652/v1.
36. ^ Afshin Rashid. (2024). *Nano Cloud Capacitor Section Nano Supercapacitors and (LSPR energy) Dielectric Nano Carbon (Active Piezoelectric Material).* doi:10.22541/au.172357736.63195078/v1.
37. ^ Afshin Rashid. (2024). *The Term "Nano-Transistor" Comes From The Combination of "Nano-scale" in Transmission And Resistance* . doi:10.22541/au.172479168.84284556/v1.
38. ^ Afshin Rashid. (2024). *Nano Transistor With Graphene Nano Sheets (GA) ,The Role of Graphene Nano-Plates (GA) in The Construction of Nano Transistors* . doi:10.22541/au.172479230.06570180/v1.
39. ^ Afshin Rashid. (2024). *Fullerenes Are Molecules in The Range of (Nanometers). Diamonds Are a Type of Fullerenes. Fullerene is The Second Best Electric Nano Semiconductor in The World.* doi:10.22541/au.172479231.12484252/v1.
40. ^ Afshin Rashid. (2024). *Diamond Nano Particles, Structure and Function* . doi:10.22541/au.172479231.19005512/v1.
41. ^ Afshin Rashid. (2024). *Application of Single-Walled and Multi-Walled CNT and CNTs Carbon Nanotubes in Aerospace industries* . doi:10.22541/au.172479395.56370423/v1.
42. ^ Afshin Rashid. (2024). *Structure and Types of Nano Reactors in the Catalytic Process of Electrical Porous Materials.* doi:10.22541/au.172479402.23796983/v1.